# MATERIAL SAFETY DATA SHEET



#### NOVUS Inc.

10425 Hampshire Avenue South Minneapolis, MN 55438

Medical Emergencies (800) 228-5635 x334 Transportation Emergencies (800) 424-9300 Outside U.S. call (703) 527-3887 collect Business Phone (952) 944-8000

### SECTION 1 - PRODUCT IDENTIFICATION AND USE

**PRODUCTNAME(S):** NOVUS Plastic Polish #2 (P/N 7030, 7032, 7033, & 7072) **NOVUS I.D.** NUMBER: 7011

CHEMICAL NAME:
NA
Clean and restore plastic surfaces.

SECTION 2 - HAZARDOUS INGREDIENTS								
INGREDIENT	% BY WEIGHT	CAS#	EXPOSURELIMITS	LD50 (SPECIES & ROUTE)	LC50 (SPECIES)			
Odorless Mineral Spirits	7-13	64742-48-9	400 ppm (5)	NE	NE			
Silica, Amorphous, Diatomaceous Earth	1 - 5 3 - 7	61790-53-2 68855-54-9	10 mg/m³ (1) 3 mg/m³ respirable (1)	NE NE	NE NE			
Crystalline Silicas	0 - 4.3	14808-60-7 14464-46-1	.05 mg/m³ (2) respirable fraction	NE	LCLo (inhl-human) 300mg/m³/10 years intermittent			
Morpholine	1-5	110-91-8	20 ppm (1,2) 30 ppm (3,4)	Rat: 1050 mg/kg Rabbit, skin: 500 mgkg	Rat: 12,000 ppm (8 hr.)			
Oleic Acid	1-5	112-80-1	NE	Rat: 20 ml/kg	NE			
Non-Hazardous: Water	60 - 70	7732-18-5						

NOTES: (1) ACGIH TLV (TWA) (2) - OSHA PEL (TWA) (3) - ACGIH STEL (4) - OSHA STEL (5) - MFR/SUPPLIER TLV LD 50 VALUES ARE VIA ORAL ROUTE UNLESS OTHERWISE INDICATED

\*\* TOXIC CHEMICAL REPORTABLE PER SECTION 313, TITLE III SARA AND 40 CFR372

SECTION 3 - PHYSICAL DATA								
PHYSICALSTATE:	Liquid	APPEARANCE:	Tan opaque liquid	ODOR: Slight solvent odor				
VAPOR PRESSURE (mmHg):	<75	% VOLATILE:	< 20	VAPOR DENSITY (AIR=1):				
EVAPORATION RATE(BuAc=1):	< 1	BOILING POINT (deg C):	80	FREEZING POINT (deg C):				
pH:	NE	DENSITY (g/ml):	1.01	SOLUBILITYIN WATER: Appreciable				
SECTION 4 - FIRE AND EXPLOSION DATA								
FLAMMABILITY_	IF YES, UNDER			NFPA Rating: 1 1 0				

#### YES NO X WHICH CONDITIONS: Carbon Dioxide, Dry Chemical, or Foam. EXTINGUISHING MEDIA: SPECIAL FIRE FIGHTING PROCEDURES: Use water spray or fog to cool fire exposed containers. FLASH POINT (PMCC) deg F: **UPPER FLAMMABILITY LIMIT:** LOWER FLAMMABILITY LIMIT: NE >200 NF (% BY VOLUME) (% BY VOLUME) **AUTOIGNITION** HAZARDOUS COMBUSTION PRODUCTS: Carbon Dioxide and Carbon Monoxide. NF TEMPERATURE (deg C): EXPLOSION SENSITIVITY TO IMPACT: SENSITIVITY TO STATIC DISCHARGE:

DATA

SENSITIVITY TO IMPACT:
NE
NE
SENSITIVITY TO STATIC DISCHARGE:
No

## **SECTION 5 - REACTIVITY DATA**

CHEMICAL STABILITY: IF NO, UNDER
YES X NO WHICH CONDITIONS:

INCOMPATIBILITY WITH OTHER SUBSTANCES:

INCOMPATIBILITY WITH OTHER SUBSTANCES:
YES X NO IF SO, WHICH ONES?

Strong oxidizers.

REACTIVITY, AND
UNDER WHICH CONDITIONS?

Product is not considered highly reactive.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon Dioxide and Carbon Monoxide.

PN 0217 REV. 3/02 NA - NOT APPLICABLE UN - UNAVAILABLE NE - NOT ESTABLISHED

PRODUCTNAME(S): NOVUS Plastic Polish #2 (P/N 7030, 7032, 7033, & 7072) SECTION 6 - TOXICOLOGICAL PROPERTIES ROUTE OF ENTRY: SKIN ABSORPTION X EYE CONTACT X INHALATION X INGESTION X SKIN CONTACT X EFFECTS OF ACUTE EXPOSURE TO PRODUCT: May cause respiratory irritation. Exposure to high concentrations may cause headache, dizziness, and nausea. Eye contact may cause burning and irritation. Skin contact is a possible route of entry. Also, see information on crystalline silica (next entry). EFFECTS OF CHRONIC EXPOSURE TO PRODUCT: Prolonged or repeated skin contact may lead to drying, irritation, and dermatitis. This product may contain crystalline silica, which is known to cause cancer by inhalation. If this product is used with mechanical polishing, dusts may be created that can be a chronic inhalation hazard. See Section 7 for measures to prevent exposure **EXPOSURELIMITS:** IRRITANCY OF PRODUCT: SENSITIZATION TO PRODUCT: **CARCINOGENICITY:** see note below under "Other Mild: Eyes, skin, and respiratory See section 2. Information" TERATOGENICITY: SYNERGISTIC PRODUCTS: REPRODUCTIVE TOXICITY: MUTAGENICITY: NE CTION 7 - PREVENTIVE MEASURES PERSONAL PROTECTIVE EQUIPMENT CLOTHING(SPECIFY): RESPIRATORY(SPECIFY): Wear chemical resistant gloves and clothing If TLV or PEL is exceeded, wear a NIOSH approved respirator for as needed to prevent skin contact. organic vapors. For mechanical polishing, wear dust mask. EYE (SPECIFY): OTHER(SPECIFY): If possible, eye wash and safety shower Wear chemical safety goggles. should be available. **ENGINEERING CONTROLS (SPECIFY):** Local exhaust may be necessary under some useage/handling conditions. Specific needs should be addressed by health/safety personnel. LEAK/SPILL PROCEDURE: Wear personal protective equipment. Remove heat and ignition sources, ventilate area, clean up with inert absorbant. WASTEDISPOSAL: Waste may be burned in an approved incinerator or disposed of according to local, state, provincial, and federal regulations. HANDLING PROCEDURES/EQUIPMENT AND STORAGE REQUIREMENTS: Store in closed container in cool, dry location, away from direct sunlight or sources of intense heat. SPECIAL SHIPPING INFORMATION: **OTHER INFORMATION:** HMIS Rating: 1 1 0 B Diatomaceous Earths may contain crystalline silica, which is considered carcinogenic by KEEP FROM FREEZING inhalation (IARC, NTP, California), However, with hand application respirable dusts are not created. Use of mechanical polishing may necessitate respiratory PPE to limit exposure. CTION 8 - FIRST AID MEASURES SYMPTOMS/EFFECTS OF OVEREXPOSURE: Respiratory irritation. High concentrations may cause headache, dizziness, and nausea. Prolonged or repeated exposure may lead to skin irritation and dermatitis. Eye contact is irritating and may cause damage. EYES: Immediately flush eyes with large amounts of water for at least 15 minutes while holding the eyelids open. Get prompt medical attention. SKIN: Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists. INHALATION: Move victim to fresh air and treat symptomatically. Seek medical attention if irritation persists. INGESTION: Contact local poison control center or physician IMMEDIATELY! SECTION 9 - MSDS PREPARATION INFORMATION THIS MATERIAL SAFETY DATA SHEET IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTENT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE. PREPARED BY: DATE: **NOVUS Inc. CHEMISTRY DEPARTMENT** 3-06-02